

## 12NC/Fx: F102295

## GTIN (EAN) code: 5054645022953

| DIMENSION  | MEAS | URI             |
|--|------|-----------------|
| OVERALL CABINET  |      |                 |
| MIN Height of the wall cabinet niche, including all required space for installation or ventilation | 0    | mm              |
| MIN Height of the tall cabinet niche, including all required space for installation or ventilation | 870  | mm              |
| MIN Height of the base cabinet niche, including all required space for installation or ventilation | 870  | mm              |
| MAX Height of the wall cabinet niche, including all required space for installation or ventilation | 0    | mm              |
| MAX Height of the tall cabinet niche, including all required space for installation or ventilation | 872  | mm              |
| MAX Height of the base cabinet niche, including all required space for installation or ventilation | 870  | mm              |
| MIN Width of the wall cabinet niche, including all required space for installation or ventilation  | 0    | mm              |
| MIN Width of the tall cabinet niche, including all required space for installation or ventilation  | 562  | mm              |
| MIN Width of the base cabinet niche, including all required space for installation or ventilation  | 562  | mm              |
| MAX Width of the wall cabinet niche, including all required space for installation or ventilation  | 0    | mm              |
| MAX Width of the tall cabinet niche, including all required space for installation or ventilation  | 568  | mm              |
| MAX Width of the base cabinet niche, including all required space for installation or ventilation  | 562  | mm              |
| MIN Depth of the wall cabinet niche, including all required space for installation or ventilation  | 0    | mm              |
| MIN Depth of the tall cabinet niche, including all required space for installation or ventilation  | 550  | mm              |
| MIN Depth of the base cabinet niche, including all required space for installation or ventilation  | 550  | mm              |
| Space in front, which is required to install bottom trim   | 10   | mm              |
| Indicates whether a ventilation opening is needed or not. Default is "N"                           | Yes  |                 |
| WALL CABINET (vent-shaft incoming)   |      |                 |
| Indicates the position of the freespace for the inbound airflow (wall cabinet)                     | Rear |                 |
| Minimum space or inbound ventilation (wall cabinet)  | 0    | mm              |
| Minimum area for inbound ventilation cavity (wall cabinet)   | 0    | cm <sup>2</sup> |
| WALL CABINET (vent-shaft outgoing)   |      |                 |
| Indicates the position of the freespace for the outbound airflow (wall cabinet)                    | Rear |                 |
| Minimum space or outbound ventilation (wall cabinet)   | 0    | mm              |
| Minimum area for outbound ventilation cavity (wall cabinet)  | 0    | cm <sup>2</sup> |
| TALL CABINET (vent-shaft incoming)   |      |                 |
| Indicates the position of the freespace for the inbound airflow (tall cabinet)                     | Rear |                 |
| Minimum space for inbound ventilation (tall cabinet)   | 50   | mm              |
| Minimum area for inbound ventilation cavity (tall cabinet)   | 281  | cm <sup>2</sup> |
| TALL CABINET (vent-shaft outgoing)   |      |                 |
| Indicates the position of the freespace for the outbound airflow (tall cabinet)                    | Rear |                 |
| Minimum space for outbound ventilation (tall cabinet)  | 50   | mm              |
| Minimum area for outbound ventilation cavity (tall cabinet)  | 281  | cm <sup>2</sup> |
| BASE CABINET (vent-shaft incoming)   |      |                 |
| Indicates the position of the freespace for the inbound airflow (base cabinet)                     | Rear |                 |
| Minimum space for inbound ventilation (base cabinet)   | 50   | mm              |
| Minimum area for inbound ventilation cavity (base cabinet)   | 281  | cm <sup>2</sup> |
| BASE CABINET (vent-shaft outgoing)   |      |                 |
| Indicates the position of the freespace for the outbound airflow (base cabinet)                    | Rear |                 |
| Minimum space for outbound ventilation (base cabinet)  | 50   | mm              |
| Minimum area for outbound ventilation cavity (base cabinet)  | 281  | cm <sup>2</sup> |

| DIMENSION ME  |     | EASURE |  |
|---|-----|--------|--|
| APPLIANCE   |     |        |  |
| Height of the front   | 882 | mm     |  |
| Width of the front  | 595 | mm     |  |
| Depth of the front  | 25  | mm     |  |
| Maximum depth all protruding elements, e.g. handles, controls   | 53  | mm     |  |
| Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees    | 41  | mm     |  |
| Projection of front in relation to housing of appliance   | 15  | mm     |  |
| Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable | 3   | mm     |  |
| When product panel is missing, set to 0   | 115 | mm     |  |
| Space in front, which is required to guarantee full operability. The most protruding part gives this dimension                  | 465 | mm     |  |
| Height from bearing area of appliances and lower handle   | 439 | mm     |  |
| Frontal handle thickness  | 25  | mm     |  |
| Frontal handle width  | 513 | mm     |  |
| MIN Height of the product body  | 867 | mm     |  |
| MAX Height of the product body  | 867 | mm     |  |
| Width of the product body   | 561 | mm     |  |
| Depth of the product body   | 550 | mm     |  |
| Full depth of product excluding protruding interface elements   | 575 | mm     |  |
| -   | -   | mm     |  |
| MIN depth between plinth return and front   | 0   | mm     |  |
| MAX depth between plinth return and front   | 0   | mm     |  |
| Height MIN Plinth return. This dimension is taken by minimum appliance height   | 0   | mm     |  |
| Height MAX Plinth return. This dimension is taken at maximum appliance height   | 0   | mm     |  |
| Appliance can be used as base for other appliances from the same manufacturer. Default is "No"                                  | No  |        |  |
| Appliance Flap door   |     |        |  |
| Projection of the opened flap in relation to bearing area   | 5   | mm     |  |
| Maximum angle when flap door is opened totally  | 89  | mm     |  |
| Appliance Side swing door   |     |        |  |
| Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted                   | 0   | mm     |  |
| Lateral projection of opened front at the side where the hinge is fixed   | 0   | mm     |  |
| Maximum angle when door is opened totally   | 0   | mm     |  |
| Appliance other   |     |        |  |
| Depth from front end of the niche to the front end of the freespace of the retrace  | 65  | mm     |  |
| Height from niche to bottom end of freespace for the retrace  | 849 | mm     |  |