

HMCB 70301 UK

12NC/Fx: F161805

DIMENSION		JRE	DIMENSION		JRE
WOODEN CABINET - Overall Wooden Cabinet - BI			APPLIANCE		
01. Height MIN of the tall cabinet Niche, including all required space for installation or ventilation	1776	mm	Overall Appliance		
(HMIN_T) 02. Height MAX of the tall cabinet Niche, including all required space for installation or ventilation	1786	mm	01. Height MIN Product, watch the detail drawing for the exact position of the dimension line (HMIP)	1770	mm
(HMAN_T)	1700		02. Height MAX product, watch the detail drawing for the exact position of the dimension line	1770	mm
03. Width MIN of the tall cabinet Niche, including all required space for installation or ventilation	560	mm	(HMAP)		
(WMIN_T)			03. Width product, watch the detail drawing for the exact position of the dimension line (WP)	540	mm
04. Width MAX of the tall cabinet Niche, including all required space for installation or ventilation (WMAN_T)	570	mm	04. Depth product without front, watch the detail drawing for the exact position of the dimension line (DP)	0	mm
05. Depth of the tall cabinet Niche, including all required space for installation or ventilation (DN_T) 550	mm	05. Depth product, watch the detail drawing for the exact position of the dimension line (D)	545	mm
06. Height MIN of the base cabinet Niche, including all required space for installation or ventilation	0		06. Depth MIN plinth return front (DMIPRF)	0	mm
(HMIN_B)	-		07. Depth MAX plinth return front (DMAPRF)	41	mm
07. Height MAX of the base cabinet Niche, including all required space for installation or ventilation	0 ו		08. Height MIN Plinth return. This dimension is taken by minimum appliance height (HMIPR)	34	mm
(HMAN_B) 08. Width MIN of the base cabinet Niche, including all required space for installation or ventilation	0		09. Height MAX Plinth return. This dimension is taken at minimum appliance height (HMAPR)	34	mm
(WMIN_B)	0		Door or Drawer		
09. Width MAX of the base cabinet Niche, including all required space for installation or ventilation (WMAN_B)	0		10. Height front. When appliance has more than one front, only the most bottom left front is discribed here (HF)	630	mm
10. Depth of the base cabinet Niche, including all required space for installation or ventilation (DN_B)	0		11. Width front. When appliance has more than one front, only the most bottom left front is discribed here (WF)	540	mm
11. Indicates whether a ventilation opening is needed or not. Default is "N"	Yes		12. Depth front (DF)	0	mm
12. Appliance can be used as base for other appliances from the same manufacturer. Default is "N"	No		13. Maximum depth all protruding elements, e.g. handles, controls (DC)	0	mm
			14. Lateral clearance between front edge and most protruding elements which avoid to open a	a 0	mm
WOODEN CABINET - Door – Drawer			neighbour front more than 90° (CC)		
13. Height MIN Decorative Front, if appliance has more than one front, only the most bottom left	970		15. Projection of front in relation to housing of appliance (FPT)	18	mm
front is described here (HMIF)		mm	16. Projection of front in relation to bearing area of the appliance. Taken at MIN height of appliance if adjustable height(FPB)	0	mm
14. Width MIN Decorative Front, if appliance has more than one front, only the most bottom left front is described here (WMIF)	560	mm	17. Height Product Panel. When product panel is missing, set to 0 (HMAPP)	57	mm
15. Weight/Thickness of the decorative bottom front panel of the Kitchen manufacturer needs (essential)	No		18. Lateral projection of front including controls when door is opened totaly. At the side where the hinge is mounted (FPOD)	0	mm
16. Weight MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMAF)	0	kg	19. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)	0	mm
17. Thickness MIN Decorative Front, if appliance has more than one front only the most bottom lef front is described here(TMIF)	10	mm	20. Lateral projection of opened front at the side where the hinge is fixed (FPD)	0	mm
18. Thickness MAX Decorative Front, if appliance has more than one front only the most bottom left front is described here(TMAF)	0	mm	21. Door hinge positiong and tipology	Right- changeable	
Additional Fronts (2 doors)			22. Type of preparation to fix the cover door	Sliding	
19. Height MIN Decorative Front, when appliance has more than one front, upper front is discribed	0			system	0
here (HMIFU)	0	mm	23. Maximum angle when door is opened totaly (AOD)	0	
20. Width MIN Decorative Front, when appliance has more than one front, upper front is discribed here (WMIFU)	0	mm	24. Maximum thickness of the upper front panel (TUFP)	4	mm
21. Weight/Thickness of the decorative upper front panel of the Kitchen manufacturer needs	No		Additional Fronts (2 doors) 25. Height front, when appliance has more than one front, upper front is discribed here (HUF)	970	mm
(essential)			26. Width front, when appliance has more than one front, upper front is discribed here (WUF)		mm
22. Weight MAX of the decorative upper front panel of the Kitchen manufacturer (WEMAFU)	0	kg	27. Useful space between the 2 doors, including hinges size (HMAFG)	540 75	mm
23. Thickness MIN Decorative Front, when appliance has more than one front, upper front is discribed here (TMIFU)	0	mm	28. Distance between the bottom of the product and the center line between the fridge doors	75	mm mm
24. Thickness MAX Decorative Front, when appliance has more than one front, upper front is	0	mm	(HFG)		

discribed here (TMAFU)		
TALL WOODEN CABINET - Vent-shaft incoming		
25. Indicates the position of the freespace for the incoming airflow, tall wooden cabinet	Front- Bottom	
26. Clearance MIN Ventilation, tall wooden cabinet (CMIV_TI)	50	mm
27. Ventilation cavity minimum, tall wooden cabinet (VC_TI)	200	Cm ²
TALL WOODEN CABINET - Vent-shaft outgoing		
28. Indicates the position of the freespace for the outgoing airflow, tall wooden cabinet	-	
29. Clearance MIN Ventilation, tall wooden cabinet (CMIV_TO)	50	mm
30. Ventilation cavity minimum, tall wooden cabinet (VC_TO)		Cm ²
BASE WOODEN CABINET - Vent-shaft incoming		
31. Indicates the position of the freespace for the incoming airflow, base wooden cabinet	-	
32. Clearance MIN Ventilation, base wooden cabinet (CMIV_BI)	0	mm
 Ventilation cavity minimum, base wooden cabinet (VC_BI) 	0	cm ²
BASE WOODEN CABINET - Vent-shaft outgoing		
34. Indicates the position of the freespace for the outgoing airflow, base wooden cabinet	-	
35. Clearance MIN Ventilation, base wooden cabinet (CMIV_BO)	0	mm
36. Ventilation cavity minimum, base wooden cabinet (VC_BO)	0	Cm ²