

MP 776 IX H

12NC/Fx: F096683

GTIN (EAN) code: 5016108966839

DIMENSION	MEAS	MEASURE	
OVERALL CABINET			
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	450	mm	
MIN Height of the base cabinet niche, including all required space for installation or ventilation	450	mm	
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	453	mm	
MAX Height of the base cabinet niche, including all required space for installation or ventilation	453	mm	
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm	
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mm	
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm	
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568	mm	
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mm	
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	550	mm	
Space in front, which is required to install bottom trim	8	mm	
Indicates whether a ventilation opening is needed or not. Default is "N"	No		
WALL CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-		
Minimum space or inbound ventilation (wall cabinet)	0	mm	
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm ²	
WALL CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-		
Minimum space or outbound ventilation (wall cabinet)	0	mm	
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm ²	
TALL CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (tall cabinet)	-		
Minimum space for inbound ventilation (tall cabinet)	0	mm	
Minimum area for inbound ventilation cavity (tall cabinet)	0	cm ²	
TALL CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-		
Minimum space for outbound ventilation (tall cabinet)	0	mm	
Minimum area for outbound ventilation cavity (tall cabinet)	0	cm ²	
BASE CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (base cabinet)	-		
Minimum space for inbound ventilation (base cabinet)	0	mm	
Minimum area for inbound ventilation cavity (base cabinet)	0	cm ²	
BASE CABINET (vent-shaft outgoing)	Ū	C.I.I	
Indicates the position of the freespace for the outbound airflow (base cabinet)	-		
Minimum space for outbound ventilation (base cabinet)	0	mm	
Minimum area for outbound ventilation cavity (base cabinet)	0	cm ²	

APPLIANCE 155 mm Height of the front 455 mm Width of the front 595 mm Depth of the front 20 mm Maximum depth all protruding elements, e.g. handles, controls 42 mm Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees 0 mm Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, it height is adjustable 95 mm When product panel is missing, set to 0 95 mm mm Space in front, which is required to guarantee full operability. The most protruding part gives this adjustable 300 mm Protel handle width 519 mm Frontal handle thickness 300 mm Frontal handle thickness 355 mm Pulpt of the product body 447 mm Mixith of the product body 553 mm Minimum height from bottom line hood to top line air outlet 0 mm Diameter minimum air outlet 0 mm Diameter maximum air outlet 0 mm Diameter maximum air outleth	DIMENSION					
Width of the front595mmDepth of the front20mmMaximum depth all protruding elements, e.g. handles, controls42mmLateral clearance between front edge and most protruding elements which avoid to open a neighbour front in relation to busing of appliance10mmProjection of front in relation to busing of appliance10mmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable00mmWhen product panel is missing, set to 095mmSpace in front, which is required to guarantee full operability. The most protruding part gives this348mmdimension300mmFrontal handle thickness300mmFrontal handle width519mmMIN Height of the product body535mmMith of the product body535mmWidth of the product body535mmFull depth of product excluding protruding interface elements554mmMinimum height from bottom line hood to top line air outlet0mmDiameter maximum air outlet0mmmmDiameter maximum air outlet0mmmmDiameter maximum air outlet0mmmmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"nmmAppliance flap doornmmmmmmDiameter maximum air outlet0mmmmmmDiameter maximum air outlet <td< th=""><th colspan="6">APPLIANCE</th></td<>	APPLIANCE					
Depth of the front20mmMaximum depth all protruding elements, e.g. handles, controls42mmLateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees0mmProjection of front in relation to busing of appliance10mmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable0mmWhen product panel is missing, set to95mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension348mmHeight from bearing area of appliances and lower handle302mmFrontal handle thickness300mmFrontal handle width519mmMIN Height of the product body447mmWidth of the product body447mmWidth of the product body553mmFull depth of product excluding protruding interface elements0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmmmDiameter minimum air outlet0mmmmAppliance Flap door1616mmAppliance Flap door161616Projection of the opened flap in relation to bearing area0mmAppliance Side swing door161616Appliance Side swing door161616Appliance Side swing door16 <t< th=""><th>Height of the front</th><th>455</th><th>mm</th></t<>	Height of the front	455	mm			
Maximum depth all protruding elements, e.g. handles, controls 42 mm Lateral clearance between front edge and most protruding elements which avoid to open a 0 mm neighbour front more than 90 degrees 10 mm Projection of front in relation to busing of appliance 10 mm appliance, if height is adjustable 0 mm When product panel is missing, set to 0 55 mm Space in front, which is required to guarantee full operability. The most protruding part gives this 348 mm dimension 348 mm mm Frontal handle thickness 30 mm Frontal handle width 519 mm MIN Height of the product body 447 mm Mith of the product body 535 mm Full depth of product excluding protruding interface elements 554 mm Minimum height from bottom line hood to pline air outlet 0 mm Diameter maximum air outlet 0 mm </td <td>Width of the front</td> <td>595</td> <td>mm</td>	Width of the front	595	mm			
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees0mmProjection of front in relation to housing of appliance10mmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable0mmWhen product panel is missing, set to 095mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension348mmHeight from bearing area of appliances and lower handle302mmFrontal handle thickness509mmFrontal handle width519mmMIN Height of the product body447mmMXA Height of the product body533mmPill depth of product excluding protruding interface elements554mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmAppliance flap doormmAppliance flap doormmProjection of the opened flap in relation to bearing area0mmAppliance flap doormmmmAppliance flap doormmmmAppliance flap doormmmmLateral projection of product sold when door is opened totaly. At the side where the hinge is fixed0mmDiameter maximum air outlet0mmmmDiameter maximum air outlet0mmmmDiameter maximum air outlet <td< td=""><td>Depth of the front</td><td>20</td><td>mm</td></td<>	Depth of the front	20	mm			
neighbour front more than 90 degrees10mmProjection of front in relation to boaring area of the appliance. Taken at minimum height of appliance, if height is adjustable0mmWhen product panel is missing, set to 095mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension348mmHeight from bearing area of appliances and lower handle302mmFrontal handle thickness300mmFrontal handle builth519mmMIN Height of the product body535mmWidth of the product body535mmWidth of the product body535mmDepth of product excluding protruding interface elements554mmMinimum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmAppliance Can be used as base for other appliances from the same manufacturer. Default is "No"-Appliance Flap door6mmProjection of the rear flap in relation to bearing area0mmMaximum angle when flap door is opened totally. At the side where the hinge is0mmAppliance Side swing door6mmAppliance Trap oportion of front incl. controls when door is opened totaly. At the side where the hinge is0mmMaximum angle when flap door is opened totally. At the side where the hinge is0mmAppliance other0mmmmMaximum angle when door	Maximum depth all protruding elements, e.g. handles, controls	42	mm			
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable0mmWhen product panel is missing, set to 095mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension348mmHeight from bearing area of appliances and lower handle302mmFrontal handle thickness30mmFrontal handle to the product body447mmMIN Height of the product body447mmWidth of the product body553mmFull depth of product body553mmFull depth of product body553mmMinimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance Side swing door55mmAppliance Side swing door55mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmmmAppliance cother0mmmmDiameter maximum and uppendor is opened totally. At the side where the hinge is fixed0mmAppliance Cother0mmmmAppliance Cother0mm		0	mm			
appliance, if height is adjustablemmWhen product panel is missing, set to 095mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension348mmHeight from bearing area of appliances and lower handle302mmFrontal handle thickness30mmFrontal handle thickness30mmMIN Height of the product body447mmMIX Height of the product body447mmWidth of the product body535mmFull depth of product body0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance Flap doorProjection of the opened flap in relation to bearing area0mmAppliance Side swing doorLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is0mmAppliance Of pened flap in telation to bearing area0mmAppliance Side swing doorLateral projection of front incl. controls when door is opened totaly. At the side where t	Projection of front in relation to housing of appliance	10	mm			
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension348mmHeight from bearing area of appliances and lower handle300mmFrontal handle thickness300mmFrontal handle width519mmMIN Height of the product body447mmMAX Height of the product body447mmWidth of the product body553mmDepth of the product body553mmMinimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmmmDiameter minimum air outlet0mmDiameter motifur and outlet0mmDiameter from bottom line hood to bearing area0mmProjection of the rear flap in relation to bearing area0mmAppliance Flap doorIIProjection of the opened flap in relation to bearing area0mmAppliance Flap doorIIProjection of the opened flap in relation to bearing area0mmAppliance Side swing doorIIILateral projection of opened front at the side where the hinge is fixed0mmAppliance other0mmMaximum angle when door is opened totally. At the side where the hinge is0Appliance other0mmMaximum angle when door is opened totally. At the side where the hinge is0mmApp		0	mm			
dimensionImage: constraint of a paper of a paper a data of a data data of a dat	When product panel is missing, set to 0	95	mm			
Frontal handle thickness30mmFrontal handle width519mmMIN Height of the product body447mmMAX Height of the product body447mmWidth of the product body553mmDepth of the product body553mmFull depth of product excluding protruding interface elements554mmMinimum height from bottom line hood to top line air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance Flap doorProjection of the opened flap in relation to bearing area0mmMaximum angle when flap door is opened totally. At the side where the hinge is fixed0mmAppliance Side swing doorLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally. At the side where the hinge is fixed0mmAppliance other0mmDepth from front end of the front end of the freespace of the retrace140mm		348	mm			
Frontal handle width 519 mm MIN Height of the product body 447 mm MAX Height of the product body 553 mm Width of the product body 553 mm Depth of the product body 535 mm Full depth of product excluding protruding interface elements 554 mm Minimum height from bottom line hood to top line air outlet 0 mm Maximum height from bottom line hood to top line air outlet 0 mm Diameter minimum air outlet 0 mm Indicates measure between center of air outlet hole and rear wall 0 mm Projection of the rear flap in relation to bearing area 0 mm Appliance Clap door - - - Projection of the opened flap in relation to bearing area 0 mm Maximum angle when flap door is opened totally - - - Appliance Side swing door - - - - Lateral projection of opened front at the side where the hinge is fixed 0 mm - Maximum angle when door is opened totally - - - - -<	Height from bearing area of appliances and lower handle	302	mm			
MIN Height of the product body447mmMAX Height of the product body553mmWidth of the product body553mmDepth of the product body535mmFull depth of product excluding protruding interface elements554mmMinimum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance Flap door0mmProjection of the opened flap in relation to bearing area0mmAppliance Side swing door6mmAppliance Side swing door0mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmAppliance other0mmmmMaximum angle when door is opened totally0mmAppliance other0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace140Maximum angle when door is opened totally0mmMaximum angle when do	Frontal handle thickness	30	mm			
MAX Height of the product body447mmWidth of the product body553mmDepth of the product body535mmFull depth of product excluding protruding interface elements554mmMinimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance Can be used as base for other appliances from the same manufacturer. Default is "No"-1Appliance Flap door111Projection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally855mmAppliance Side swing door111Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmmmAppliance other0mmmmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally<	Frontal handle width	519	mm			
Width of the product body553mmDepth of the product body535mmFull depth of product excluding protruding interface elements554mmMinimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance Can be used as base for other appliances from the same manufacturer. Default is "No"Appliance Flap door0mmMaximum angle when flap door is opened totally85mmAppliance Side swing door0mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmmmMaximum angle when door is opened totally0mmmmAppliance other0mmmmMaximum angle when door is opened totally0mmMaximum angle w	MIN Height of the product body	447	mm			
Depth of the product body535mmFull depth of product excluding protruding interface elements554mmMinimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"Appliance Flap door-mmProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totallyMmAppliance Side swing doorLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is ismm-Maximum angle when door is opened totally0mmAppliance other0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totallyLateral projection of opened front at the side where the hinge is fixed0mmDiaterer projection of opened front at the side where the hinge is fixed0mmDiaterer projection of op	MAX Height of the product body	447	mm			
Full depth of product excluding protruding interface elements554mmMinimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"Appliance Flap doorProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing doorLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmmmAppliance other0mmDateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmmmMaximum angle when door is opened totally0mmmmDateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmmmDateral projection of opened front at the side where the hinge is fixed<	Width of the product body	553	mm			
Minimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"-Projection of the opened flap in relation to bearing area6mmAppliance Flap doorProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing doorLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMmMaximum angle when door is opened totally0mmLateral projection of front int the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDiatered front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDiatered from front end of the niche to the front end of the freespace of the retrace140	Depth of the product body	535	mm			
Maximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"Appliance Flap doormmProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing doormmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDiateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally <td>Full depth of product excluding protruding interface elements</td> <td>554</td> <td>mm</td>	Full depth of product excluding protruding interface elements	554	mm			
Diameter minimum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"-Appliance Flap doorProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing door6mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmLateral projection of poened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDiameter0mmMaximum angle when door is opened totally1mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally1mmMaximum angle when door is opened totally1mmMaximum angle when door is opened to	Minimum height from bottom line hood to top line air outlet	0	mm			
Diameter maximum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"Appliance Flap doorProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing doorLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDiateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace140mm	Maximum height from bottom line hood to top line air outlet	0	mm			
Indicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"Appliance Flap door10mmProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing door11Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace140mm	Diameter minimum air outlet	0	mm			
Projection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"Appliance Flap doorIm-ImProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing doorImImLateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace140mm	Diameter maximum air outlet	0	mm			
Height tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"Appliance Flap doorProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing doorLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace140mm	Indicates measure between center of air outlet hole and rear wall	0	mm			
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"Appliance Flap doorImImImProjection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing doorImImLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace140mm	Projection of the rear flap in relation to bearing area	0	mm			
Appliance Flap doorImage: Second	Height tube connection for air outlet	0	mm			
Projection of the opened flap in relation to bearing area6mmMaximum angle when flap door is opened totally85mmAppliance Side swing door11Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace140mm	Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	-				
Maximum angle when flap door is opened totally 85 mm Appliance Side swing door 85 mm Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted 0 mm Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Appliance Flap door					
Appliance Side swing door Image: Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted 0 mm Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other 0 mm Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Projection of the opened flap in relation to bearing area	6	mm			
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmAppliance other0mmDepth from front end of the niche to the front end of the freespace of the retrace140	Maximum angle when flap door is opened totally	85	mm			
mountedImage: Second secon	Appliance Side swing door					
Maximum angle when door is opened totally 0 mm Appliance other 0 mm Depth from front end of the niche to the front end of the freespace of the retrace 140 mm		0	mm			
Appliance other Image: Constraint of the number of the front of the freespace of the retrace 140 mm	Lateral projection of opened front at the side where the hinge is fixed	0	mm			
Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Maximum angle when door is opened totally	0	mm			
	Appliance other					
Height from niche to bottom end of freespace for the retrace 391 mm	Depth from front end of the niche to the front end of the freespace of the retrace	140	mm			
	Height from niche to bottom end of freespace for the retrace	391	mm			