

Serie | 2, Gas hob, 60 cm, Stainless steel PBP6B5B60



Gas hob with side-mounted controls: the desired cooking zones can be conveniently operated from the side.

- Continuous cast-iron finish pan supports: for maximum stability.
- **Biomethane-ready:** your gas hob can also be powered with renewable biomethane gas.
- Ergonomic control knobs with raised center for precise adjustments.
- Surface colour: elegant stainless-steel design.
- The seamless, one-piece stainless steel design makes cleaning simple

Technical Data

Product name/family : gas hob w integrated controls Construction type : Built-in Energy input : Gas Total number of positions that can be used at the same time : 4 Type of control setting devices : sword knobs Required niche size for installation (HxWxD) : 45 x 560-562 x 480-492 mm Width of the appliance : 580 mm Dimensions : 56 x 580 x 510 mm Dimensions of the packed product (HxWxD) : $141 \times 651 \times 578$ mm Net weight : 7.1 kg Gross weight : 8.0 kg Residual heat indicator : without Location of control panel : Hob lateral Basic surface material : Stainless steel Color of surface : Stainless steel Approval certificates : CE, Eurasian Length of electrical supply cord : 100 cm EAN code : 4242002821221 Electrical connection rating : 1 W Gas connection rating : 7400 W Fuse protection : 3 A Voltage : 220-240 V Frequency : 60; 50 Hz





Serie | 2, Gas hob, 60 cm, Stainless steel PBP6B5B60

Gas hob with side-mounted controls: the desired cooking zones can be conveniently operated from the side.

Design

- Stainless steel surface
- cast iron finish pan supports with rubber feet

Usage convenience

- Design co-ordinated control dials: access knobs on the side with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 gas burners:
- Left front: high-speed burner up to 3 kW (depending on gas type)
- Left rear: Standard burner up to 1.7 KW (depending on gas type)
- Right rear: standard burner up to 1.7 KW (depending on gas type)
- Right front: economy burner up to 1 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE) NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas 50 mbar Liquid gas G30 37 mbar (PL)
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 56 x 580 x 510
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.4 KW



Serie | 2, Gas hob, 60 cm, Stainless steel PBP6B5B60

